

Fire Door Light Frame

Patent No. 8,156,699B2

UL & WHI Listed

Meets UL10B requirements for NEGATIVE PRESSURE and UL10C for POSITIVE PRESSURE.
Fire tested WITHOUT glazing compound,
tape or intumescent.

For standard 1 3/4" Door and 1/4" Glass and some other applications

ORDER INFORMATION:

Order size = Inside dimension of frame, (W+H)

Cutout size = Order size + 1 1/2"

Glass size = Order size + 3/4" (tolerance (+0/-1/16))

MATERIAL:

18 GA. CRS frame is standard.

- 33% thicker than 20 GA. frames.
- Maintains flat appearance.

STANDARD FINISHES:

Beige, gray or dark bronze polyester powder coating.

- Extremely durable
- Visually appealing

NARROW FACE FRAME:

- Better proportioned
- Visually appealing
- Suitable for wood, metal or mineral core doors.

OPTIONS:

- 18 GA. Galvanized.
- 18 GA. Stainless Steel.
- Custom colors.
- Wood veneer wrapped in various species to match door.
- Maximum Glass pocket is 5/8" less than door thickness
- Available for a variety of glass or door thicknesses (for an upcharge)

MOUNTING HOLES:

- 11" length or less, one hole centered.
- Over 11", three inches, maximum from corners.
11 5/16" maximum centers.

GLASS NOTE: For non-fire rated applications we recommend 1/4" tempered glass. If laminated glass is used, glazing tape and light torque on the screws is required to prevent glass breakage.

